

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 1/17

Replaced revision:3 (Dated: 31/08/2021)

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 84022

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml Product name

UFI: AA4C-M0SS-700A-5W60

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Aerosol Jubricant.

Identified Uses	_Industrial	Professional	Consumer	
Consumer	-	-	✓	
Industrial Use	~	-	-	
Professional Use	-	✓	-	
1.3. Details of the supplier of the	safety data sheet			

Name G&B Fissaggi Srl

Full address Corso Savona, 22 10029 Villastellone (TO) District and Country Italia

tel. +39 011.961.94.33 fax +39 011.961.93.82

tecnico@gebfissaggi.com e-mail address of the competent person.

responsible for the Safety Data Sheet G&B Fissaggi Srl

1.4. Emergency telephone number

For urgent inquiries refer to

- IT Centro Antiveleni e Centro Nazionale di Informazione Tossicologica: Tel. 0382 24444 (IRCCS Fondazione Salvatore Maugeri Pavia)
- IT Centro Antiveleni di Milano: Tel. 02 66101029 (Ospedale Niguarda Ca' Granda Milano)
- IT Centro Antiveleni di Roma: Tel. 06 3054 343 (Policlinico Universitario A. Gemelli IRCCS Roma)
- IT Centro Antiveleni di Bergamo: Tel. 800 883300 (ASST Papa Giovanni XXIII Bergamo)
- IT Centro Antiveleni di Firenze: Tel. 055 794 7819 (Azienda Ospedaliera Universitaria Careggi Firenze)
- IT Centro Antiveleni di Napoli: Tel. 081 5453333 (Azienda Ospedaliera A. Cardarelli Napoli)
- AT Vergiftungsinformationszentrale (VIZ): Tel. +43 01 406 4343 (Austria)
- BE Belgisch Antigifcentrum: Tel. 070 245245 (Belgium)
- BG НАЦИОНАЛЕН ЦЕНТЪР ПО ТОКСИКОЛОГИЯ: Tel. +359 2 9154 233 (Bulgaria)
- HR Centar za kontrolu otrovania: Tel. +385 1 2348342 (Croatia)
- CY Τμήμα Επιθεώρησης Εργασίας (TEE): Tel. 1401 (Cyprus)
- CZ Toxikologické informační středisko (TIS): Tel. +420 224 919 293 or +420 224 915 402 (Czech Republic)
- DK Giftlinjen: Ring 82 12 12 12 (Denmark)
- EE Mürgistusteabekeskus: Tel. 16662 (Estonia)
- FI Myrkytystietokeskus: Tel. 0800 147 111 or 09 471 977 (Finland)
- FR ORFILA (INRS): Tél. +33 (0) 1 45 42 59 59 (France)
- DE Giftnotruf der Charité Universitätsmedizin Berlin: Tel. +49 030 19240 (Germany)
- GR Κέντρο Δηλητηριάσεων: Τηλ. 210 7793777 (Greece)
- HU Egészségügyi Toxikológiai Tájékoztató Szolgálat (ETTSZ): Tel. +36 80 20 1199 (Hungary)
- IS Eitrunarmiðstöð: Tel. 543 2222 (Iceland)
- IE National Poisons Information Centre (NPIC): Tel. 01 8092566 or 01 8379964 (Republic of Ireland)
- LV Latvian Poisons Information Centre: Tel. +371 67042473 (Latvia)
- LT Apsinuodijimų Informacijos biuras: Tel. 8-5 236 2052 (Lithuania)



Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 2/17

Replaced revision:3 (Dated: 31/08/2021)

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

LU - Giftinformationszentrum: Tel. +352 8002 5500 (Luxembourg)

NL - Nationaal Vergiftigingen Informatie Centrum (NVIC): Tel. 030 274 88 88 (Netherlands)

NO - Giftinformasjonen: Tel. 22 9 13 00 (Norway)

PL - Pomorskie Centrum Toksykologii: Tel. +58 682 04 04 (Poland)

PT - Centro de Informação Antivenenos (CIAV): Tel. 800 250 250 (Portugal)

RO - Biroul RSI Si Informare Toxicologica: Tel. 021 318 36 06 (Romania)

SK - Národné Toxikologické informačné centrum (NTIC): Tel. 02 5477 4166 (Slovakia)

SI - Center za klinično toksikologijo in farmakologijo: Tel. 112 (Slovenia)

ES - Servicio de Información Toxicológica (SIT) España: Tel.+34 91 562 04 20 (Spain)

SE - Giftinformationscentralen: Tel. 112 (Sweden)

CH - Schweizerisches Toxikologisches Informationszentrum (STIZ): Tel. +41 145 (Switzerland)

GB - National Poisons Information Service (NPIS) Tel. 0344 892 0111 (United Kingdom)
Members of the Public: NHS 111 (England), NHS 24 (Scotland) or NHS Direct
(Wales)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1 H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.

P102 Keep out of reach of children.

P211 Do not spray on an open flame or other ignition source.



Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 3/17

Replaced revision:3 (Dated: 31/08/2021)

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

P501

Dispose of contents/container in accordance with local regulations.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification Classification (EC) 1272/2008 (CLP) x = Conc. %

Hydrocarbons, C10-C13, nalkanes, isoalkanes, cyclics, <2%

aromatics

INDEX - $51 \le x < 55$ Asp. Tox. 1 H304, EUH066

EC 918-481-9

CAS -

REACH Reg. 01-2119457273-39-

XXXX **Propane**

 $19 \le x < 23$ INDEX 601-003-00-5 Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to

Annex VI to the CLP Regulation: U EC 200-827-9

CAS 74-98-6

REACH Reg. 01-2119486944-21-

0046

Butane

INDEX 601-004-00-0 Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to $9 \le x < 11$

Annex VI to the CLP Regulation: C, U

EC 203-448-7 CAS 106-97-8

REACH Reg. 01-2119474691-32-

XXXX

Distillates (petroleum), hydrotreated light naphthenic

INDEX 649-466-00-2 $7 \le x < 9$ Asp. Tox. 1 H304, Classification note according to Annex VI to the CLP

Regulation: L Asp. Tox. 1 H304: ≥ 40%

CAS 64742-53-6

EC 265-156-6

REACH Reg. 01-2119480375-34-

XXXX Isobutane

INDEX 601-004-00-0 $1 \le x < 3$ Flam. Gas 1A H220, Press. Gas H280

EC 200-857-2 CAS 75-28-5

REACH Reg. 01-2119485395-27-

Distillates (petroleum), hydrotreated light paraffinic



Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 4/17

Replaced revision:3 (Dated: 31/08/2021)

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

INDEX 649-468-00-3

 $0 \le x < 0.5$

Asp. Tox. 1 H304, Classification note according to Annex VI to the CLP

Regulation: L

EC 265-158-7 CAS 64742-55-8

REACH Reg. 01-2119487077-29-

XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 31,70 %

Distillates (petroleum), hydrotreated light naphthenic

* DECLL (CLP): This substance is classified according to note L of Annex VI of

CE regulation 1272/2008. Classification as a carcinogen is not necessary if one can

demonstrate that the substance contains less than 3% DMSO extract according to IP 346 measurement

"Determination of polycyclic aromatics in unused lubricating base oils and petroleum fractions

without asphaltene - dimethyl sulfoxide extraction ", Institute of Petroleum, London. This note

only applies to certain petroleum-derived compound substances contained in Part 3.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHĂLATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.



GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 5/17

Replaced revision:3 (Dated: 31/08/2021)

GENERAL INFORMATION

5.3. Advice for firefighters

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:



France

Ελλάδα

Portugal

Polska

Slovensko

Magyarország

DEU

GRC

HUN

PRT

POL

SVK

G&B FISSAGGI SRL

Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 6/17

Replaced revision:3 (Dated: 31/08/2021)

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

Deutschland Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher

Arbeitsstoffe, Mitteilung 56

FSP Límites de exposición profesional para agentes químicos en España 2021 España FRA

Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS

Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή

μεταλλαξιγόνους παράγοντες κατά την εργασία``»

Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők

hatásának kitett munkavállalók egészségének és biztonságának védelméről Decreto Legislativo 9 Aprile 2008, n.81

ITA Italia

Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes

químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos

Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie

w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w

środowisku pracy NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred trzikami svivisiacimi s

expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov

GBR United Kingdom EH40/2005 Workplace exposure limits (Fourth Edition 2020) ΕU

Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; OEL EU

Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive

2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.

TLV-ACGIH **ACGIH 2021**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Predicted no-effect concentration - PNEC

Normal value for the atmosphere

NPI

Propane						
Threshold Limit Value						
Туре	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1800	1000	7200	4000	
MAK	DEU	1800	1000	7200	4000	
VLA	ESP		1000			
TLV	GRC	1800	1000			
NDS/NDSCh	POL	1800				

Butane						
Threshold Limit Value)					
Туре	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	2400	1000	9600	4000	
MAK	DEU	2400	1000	9600	4000	
VLA	ESP		1000			Gases
VLEP	FRA	1900	800			
TLV	GRC	2350	1000			
AK	HUN	2350		9400		
NDS/NDSCh	POL	1900		3000		
WEL	GBR	1450	600	1810	750	
WEL	GBR		4			RESP
TLV-ACGIH					1000	



Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 7/17

Replaced revision:3 (Dated: 31/08/2021)

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

Distillates (petroleum), hydrotreated light naphthenic

Predicted no-effect concentration - PNEC

9.33

mg/kg

systemic

Normal value for the food chain (secondary poisoning) Health - Derived no-effect level - DNEL / DMEL

Effects on

Effects on workers

consumers Route of exposure Acute local

Chronic

mg/m3

Acute Chronic local

Acute systemic Chronic local

systemic

Chronic systemic

Inhalation

5.4 mg/m3 8h

Isobutane

Threshold Limit Value

Type Country TWA/8h

ma/m3

STEL/15min mag

Acute local

Remarks / Observations

TLV-ACGIH

800

mag

Distillates (petroleum), hydrotreated he

Туре	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	5		10		
TLV	GRC	5				
AK	HUN	5				
VLEP	ITA	5				INHAL
VLE	PRT	5		10		
NDS/NDSCh	POL	5				
NPEL	SVK	1		3	15	

Normal value for the food chain (secondary poisoning)

Distillates (petroleality, i	iyaron catca ngi	it parairii
Threshold Limit Value		
Туре	Country	TWA/8h

			mg/ms	ppiii	mg/ms
	OEL	EU	5		10
1	Dradiated as affect concentration	DNIEC			

Predicted no-effect concentration - PNEC

Normal value for the food chain (secondary poisoning)

9,33

STEL/15min

9,33

mg/kg

ppm

mg/kg

Remarks / Observations

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls



Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 8/17

Replaced revision:3 (Dated: 31/08/2021)

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	aerosol	
Colour	straw yellow	
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	flammable gas	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	< 0 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
рН	not available	Reason for missing data:substance/mixture is non-polar/aprotic (eg: an organic solvent
Kinematic viscosity	not available	mixture)
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density Relative vapour density	0, 70 ÷ 0,74 kg/l not available	Temperature: 20 °C
Particle characteristics	not applicable	



Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 9/17

Replaced revision:3 (Dated: 31/08/2021)

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU) 93,40 % - 672,48 g/litre

Explosive properties not applicable
Oxidising properties not applicable

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Avoid overheating.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information



Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 10/17

Replaced revision:3 (Dated: 31/08/2021)

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

Information not available					
Information on likely routes of exposure					
Information not available					
Delayed and immediate effects as well as chronic effects from sh	ort and long-term exposure				
Information not available					
Interactive effects					
Information not available					
ACUTE TOXICITY					
ATE (Inhalation) of the mixture: ATE (Oral) of the mixture: ATE (Dermal) of the mixture:	Not classified (no significant component) Not classified (no significant component) Not classified (no significant component)				
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics					
LD50 (Dermal): LD50 (Oral): LC50 (Inhalation vapours):	2000 mg/kg bw rat > 5000 mg/kg bw rat > 4 mg/l/4h rat				
Propane					
LC50 (Inhalation mists/powders):	800000 ppm 15 min				
Butane					
LC50 (Inhalation mists/powders):	> 1442,738 mg/l/15min rat				
Distillates (petroleum), hydrotreated light naphthenic					
LD50 (Dermal): LD50 (Oral): LC50 (Inhalation vapours):	3500 mg/kg bw rabbit 5000 mg/kg bw rat 3,85 mg/l/4h rat				
Isobutane					
LC50 (Inhalation mists/powders):	> 1442,738 mg/l/15min rat				
Distillates (petroleum), hydrotreated light paraffinic					



GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 11/17

Replaced revision:3 (Dated: 31/08/2021)

LD50 (Dermal): LD50 (Oral): LC50 (Inhalation vapours):

3500 mg/kg bw rabbit 5000 mg/kg bw rat 3,85 mg/l/4h rat

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class



Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 12/17

Replaced revision:3 (Dated: 31/08/2021)

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

ASPIRATION HAZARD

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Chronic NOEC for Algae / Aquatic Plants 1000 mg/l 72 hours

Butane

LC50 - for Fish > 24,11 mg/l/96h

Propane

LC50 - for Fish 85,82 mg/l/96h EC50 - for Crustacea 41,82 mg/l/48h

Isobutane

LC50 - for Fish > 24,11 mg/l/96h

12.2. Persistence and degradability

Propane

Global Warming Potential (GWP): 3. Ozone Depletion Potential (ODP): 0.

Distillates (petroleum), hydrotreated light

naphthenic

Degradability: information not available

Echa sources

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Rapidly degradable

But failing the 10-day window (100%).

Butane

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

Propane

Solubility in water 0,1 - 100 mg/l

Rapidly degradable



GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 13/17

Replaced revision:3 (Dated: 31/08/2021)

Rapidly degradable

Distillates (petroleum), hydrotreated light

paraffinic

Isobutane

Degradability: information not available

12.3. Bioaccumulative potential

Butane

Partition coefficient: n-octanol/water 1,09

Propane

Partition coefficient: n-octanol/water 1,09

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Product residues are to be considered special hazardous waste.

Empty cans, even if completely emptied, must not be dispersed in the environment.

The aerosol container overheated to a temperature above 50 °C may burst even if it contains a small residue of gas.

Disposal must take place in an authorized place and in compliance with the laws in force.

The transport of waste may be subject to ADR.

European waste catalog code (contaminated containers):

Aerosol as domestic waste is excluded from the application of the aforementioned rule.

The exhausted aerosol for professional / industrial use can be classified:

15.01.11 *: metallic packaging containing dangerous solid porous matrices, including empty pressure containers.



Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 14/17

Replaced revision:3 (Dated: 31/08/2021)

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

14.1. UN number or ID number

ADR / RID, IMDG, IATA:

1950

14.2. UN proper shipping name

ADR / RID:

AEROSOLS

SECTION 14. Transport information

IMDG:

AEROSOLS

IATA:

AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID:

Class: 2

Label: 2.1

IMDG:

Class: 2

Label: 2.1

IATA:

Class: 2

Label: 2.1



14.4. Packing group

ADR / RID, IMDG, IATA:

14.5. Environmental hazards

ADR / RID:

NO

IMDG: IATA:

NO NO

14.6. Special precautions for user

ADR / RID:

HIN - Kemler: --

Limited Quantities: 1 Tunnel restriction code: (D)

Packaging

instructions:

IMDG:

EMS: F-D, S-U

Special provision: -

Limited Quantities: 1

IATA:

Cargo:

Pass.:

Maximum

quantity: 150

Kg Maximum 203 Packaging instructions:

quantity: 75 Kg

A145, A167,

203

Special provision:

A802

14.7. Maritime transport in bulk according to IMO instruments



Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 15/17

Replaced revision:3 (Dated: 31/08/2021)

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point

int

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

40

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A Flammable gas, category 1A



Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 16/17

Replaced revision:3 (Dated: 31/08/2021)

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

Aerosol 1 Aerosol, category 1
Aerosol 3 Aerosol, category 3
Press. Gas (Liq.) Liquefied gas
Press. Gas Pressurised gas

Asp. Tox. 1 Aspiration hazard, category 1
H220 Extremely flammable gas.
H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)



Revision nr. 4

Dated 06/12/2022

Printed on 15/12/2022

Page n. 17/17

Replaced revision:3 (Dated: 31/08/2021)

GT - 10F LUBRICANT HQ 10 FUNCTIONS 400 ml (Cod. 84022)

- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review: The following sections were modified: 01 / 08 / 09 / 15.